



1 ANCHOR= 1 part 1+1 part 2
 SUPPLIED ASSEMBLED TOGETHER IN ORDER TO
 MAKE THE INSTALLATION EASIER



This system corresponds to one set composed of 2 parts assembled together with a double articulation like a jaw



RSA. 8 (45) -140 / 135 / 30- 310

TYPE	Ø	Ange A	LENGTH B	LENGTH C	LENGTH E	ALLOY
RSA. 8 (45)	8	45	-140	/ 135	/ 30-	310

Anchors are manufactured with a DIN EN 10278 (DIN 671) cold drawn wire, by robots using hydraulic tools. That allows minimizing bend marking and avoids micro cracks

www.anchorsforrefractory.com
 contact@anchorsforrefractory.com



Tél : + 33 3 66 50 00 33 / +33 7 85 06 29 49
 PA Vallée de l'Escaut - rue de la crête - 59264 ONNAING-France

These informations are general informative indications. Many particular conditions of use and exceptions exist in industrial applications, many parameters can influence the technical choices. The informations mentioned in this technical data sheet, in particular regarding the features and the performances of the products, is provided for guidance purposes only and is liable to change depending of the conditions of use and environment. Information mentioned can be modified without notice. The company ANCHORS will in no circumstances be held liable for the consequences of any improper use. If you want some suggestions from us, applicable for your specific application and/or environment, please contact us.